

FUJIAN JIALONG ADHESIVE TAPE CO., LTD.

NO.11 XIAZHAI ROAD, JIULONG INDUSTRY PARK, HUA AN ECONOMIC DEVELOPMENT ZONE, HUA AN COUNTY, ZHANGZHOU CITY, FUJIAN 363000 CHINA Tel:+86-596-728-0001 Fax:+86-596-728-0003 http://www.il3tape.com/

JLN-8750 (Natural)

PRODUCT DESCRIPTION

3-Way Fiberglass Reinforcing Diamond Pattern Recommended for use on light weight to average cartons up to 31 pounds (14 kg)

JLN-8750 Water-activated					
reinforced kraft paper tape is a					
green environmental protection					
product, is the national and					
provincial new products, and its					
base material and adhesive will not					
cause pollution to the environment					
and can recycling use with the					
packaging. It is mainly used to					
replace pressure sensitive adhesive					
tape, etc. Used for carton sealing.					

USE METHOD

Only use damp cloth or sponge wet wipe the face with adhesive (or the part which need be pasted up) then can paste up. Can not wipe too much water or wipe water again and again, press it after paste up. Or use the machine which is specialized in wipe water.

STORAGE CONDITION

It's recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be 4 to $26 \,^{\circ}\text{C}$ and the humidity shall be between 40% and 50%. Rotate inventory recommended.

Physical Properties		Standard	Metric	Test Method	
Color		Natural			
Laminating Adhesive		Hot Melt Adhesive: 25 g/m²			
Water-Activated Adhesive		Starch Adhesive: 20 g/m²			
Total Thickness		5.9 mils	0.15 mm	ASTM D-3652	GB/T7125
Tensile Strength	MD	70 lbs/in	310 N/25mm	ASTM D-3759	GB/T7753
	CD	21 lbs/in	95 N/25mm	ASTM D-3759	GB/T7753
Reinforcement	MD	(1-1-1-1) 75 Fiberglass per 72mm			
	CD	(1-1-1-1) 150 Fiberglass, 1" spacing, at 45° angle			
Backing		Top Ply: 25 lb (40 g/m²) Natural Virgin Kraft Paper (virgin fibers)			
		Bottom Ply: 25 lb (40 g/m²) Natural Virgin Kraft Paper (virgin fibers)			

Other dimensions available upon request.

The above properties and results obtained refer to the average values of laboratory testing carried out on the samples of JIALONG product. JIALONG does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. JIALONG strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. JIALONG assumes no responsibility for any damage or injury sustained as a result of the use of its products.

BRANCHES:

SHANGHAI JIALONG FIBER TAPE CO.,LTD.

No.211, Yuxin Rd, Songjiang Dist, Shanghai, China

JIALONG GROUP PTY LTD.

Unit 83, 79 St Hilliers Road Auburn NSW 2144, Australia.









