




## JLN-2740HD

### SELF-ADHESIVE KRAFT PAPER TAPE

| Physical Properties | Standard                  | Metric    | Test Method |             |
|---------------------|---------------------------|-----------|-------------|-------------|
| Color               | Brown                     |           |             |             |
| Adhesive            | Hot Melt Adhesive         |           |             |             |
| Backing             | 70 g/m² Brown Kraft paper |           |             |             |
| Total Thickness     | 4.9 mils                  | 0.125 mm  | ASTM D-3652 | GB/T7125    |
| Peel Adhesion 90°   | 75 oz/in                  | 21 N/25mm | ASTM D-3330 | GB/T2792    |
| Holding Power       | 24±5 h                    | 24±5 h    | ASTM D-3654 | GB/T4851    |
| Tensile Strength    | 20 lbs/in                 | 90 N/25mm | ASTM D-3759 | GB/T7753    |
| Elongation at Break | 1.5-3%                    | 1.5-3%    | ASTM D-3759 | GB/T7753    |
| Service Tem.--Mini  | 23°F                      | -5°C      | BC/BD-220SE | BC/BD-220SE |
| Service Tem.--Max   | 140°F                     | 60°C      | DHG-9055A   | DHG-9055A   |

#### Description :

JLN-2740HD is a plastic-free, self-Adhesive kraft paper tape that can be written on with markers. This pressure-sensitive tape provides reliable, quick-to-apply, and cost-effective sealing, making it an efficient solution for packaging lines. Its strong initial tack and excellent sealing performance enhance security and help reduce the risk of tampering or theft.

#### Use Method:

Tear the tape and apply directly to seal the top and bottom of cartons. Suitable for all types of cartons.

#### Shelf Life:

Up to one years from the date of shipment with proper storage.

#### Storage Condition :

It is recommended to store the product in a clean, dry environment to prevent packaging damage. Avoid placing it near volatile solvents. The optimal storage temperature is between 39-79°F (4-26°C), with a relative humidity of 40%-50%. Rotate inventory regularly to maintain product quality.

The test results provided above represent average values obtained under laboratory conditions and are intended for general reference only. JL3 does not guarantee the accuracy, completeness, or performance consistency of these results. These values do not constitute a warranty, either express or implied, including but not limited to warranties of performance, safety, or fitness for a particular purpose—whether the product is used alone or in combination with other materials. JL3 strongly recommends that users conduct independent testing to determine the product's suitability for their specific application prior to use. JL3 assumes no liability for any damage, loss, or injury arising from the use of this product. All sales are subject to JL3's standard terms and conditions. Product specifications and information are subject to change without prior notice.

#### Fujian Jialong Adhesive Tape Co.,Ltd.

No. 11 Xiazhai Road, Jiulong Industrial Park, Hua An Economic Development Zone, Hua An, Zhangzhou, Fujian 363000 China.

Tel:+86 596-728-0001

info@jl3tape.com

http://www.jl3tape.com

