



KN-1717U SEMI-AUTOMATIC WAT CASE SEALER

Take the first step toward WAT automation with the Kingnode **KN-1717U** semi-automatic case sealer. Designed for performance, the **KN-1717U** combines the ease of a pressure-sensitive hot melt case sealer with the strength and security of reinforced WAT. Its top and bottom sealers can run together or independently, with quick manual adjustments to fit various box sizes. A gravity-fed water tank offers mobility, while the brushless water system minimizes residue and downtime. Featuring an intuitive touchscreen and low water level alert, the **KN-1717U** delivers fast, flawless, and secure seals—every time.

Product Highlights



User-Friendly
Touchscreen



Low Water
Level Alert



Magnetic
Power Brake



Versatility in
Tape Size



Easy Setup &
Maintenance



E-commerce Logistics



Factories



Logistics Centers

SCAN FOR INFO

Tel: +86-592-207-5506 Email: info@jl3tape.com www.jl3tape.com
Address: No.11 Xiazhai Road, Hua An Economic Development Zone, Zhangzhou, Fujian 363000



Features & Benefits

- 01
- User-friendly operation featuring an intuitive touchscreen, water level indicators, and multiple emergency shut-off points for safe use.
- 02
- True plug-and-play design — requires only a standard electrical outlet, with no air or water line connections needed.
- 03
- Smooth, quiet tape feeding and sealing achieved with magnetic retention, eliminating reliance on standard spring mechanisms.
- 04
- Flexible sealing options — top and bottom sealers can operate simultaneously or independently to suit your needs.
- 05
- High-capacity tape rolls up to 500 mm in diameter and 1,300 m in length, minimizing tape changeovers.
- 06
- Versatile roll compatibility, supporting core diameters from 1.5" and 3".
- 07
- Efficient gravity-fed water system with a 2L (68 oz) reservoir to maximize uptime.
- 08
- Low water level alert ensures consistent wetting for a perfect seal every time.
- 09
- Durable side conveyor belts deliver strong carton stability during operation.
- 10
- Simple manual adjustments for carton height and width enable quick setup.
- 11
- Heavy-duty casters with adjustable legs provide optimal machine alignment and improved efficiency.
- 12
- Low-maintenance design, including a quick-change blade replacement mechanism.
Throughput of 8–13 cases per minute, depending on carton size.

Specifications

PRODUCT	KN-1717U SEMI-AUTOMATIC WAT CASE SEALER
Min Case (L x W x H)	5.9" × 5.9" × 5" (150 mm × 150 mm × 127 mm)
Max Case (L x W x H)	Inf × 17" × 17" (Inf × 430 mm × 430 mm)
Case Weight	max. 85 lbs (38 kg)
Belt Speed	72 ft/min (22 m/min)
Electric/Pneumatic	110 V, 60 Hz, 10 Amps, Single Phase or 220 V, 50 Hz/60 Hz, 5 Amps, Single Phase
Tape Width	2.4"- 3" (60 mm - 76 mm)
Conveyor Height	28" - 32 " (71 cm - 82 cm)
Machine Weight	750 lbs (340 kg)
Machine Dimension	93" × 43.9" × 65" (2360 mm × 1120 mm × 1650 mm)
Water Reservoir Capacity	2L

SCAN FOR INFO

