



JLN-28160E

SELF-ADHESIVE KRAFT PAPER TAPE

Physical Properties		Standard	Metric	Test Method		
Color		Brown				
Composite Layer Adhesive		Polymeric Copolymer				
Adhesive		Hot Melt Adhesive				
Total Thickness		6.3 mils	0.16 mm	ASTM D-3652	GB/T7125	
Peel Strength 90°		90 oz/in	25 N/25mm	ASTM D-3330	GB/T2792	
Retention		24±5 h	24±5 h	ASTM D-3654	GB/T4851	
Tensile Strength		38 lbs/in	170 N/25mm	ASTM D-3759	GB/T7753	
Extensibility		3-5%	3-5%	ASTM D-3759	GB/T7753	
Low Temperature		23°F	-5°C	BC/BD-220SE	BC/BD-220SE	
High Temperature		140°F	60°C	DHG-9055A	DHG-9055A	
Reinforcement	MD	(1-1-1-1-1-1) 300D Plant Fiber Yarn per 72mm				
	CD	(1-1-1) 200D Plant-Based Yarn Diamond Pattern				
Backing		Top Ply: 25 lb (40 g/m²) Brown Kraft Paper				
		Bottom Ply: 25 lb (40 g/m²) Brown Kraft Paper				

Description :

JLN-28160E is a plastic-free and degradable self-Adhesive kraft paper tape that reinforced by degradable plant based yarn. It's also a fast, reliable sealing and pressure-sensitive flatback tape, Its strong initial tack and excellent sealing performance, combined with unique reinforced plant based yarn technology, deliver greater tensile strength than general tapes—enhancing security and reducing the risk of tampering or theft.

Use Method:

Tear the tape and apply directly to seal the top and bottom of cartons. Suitable for all types of cartons.

Shelf Life:

Up to one years from the date of shipment with proper storage.

Storage Condition :

It is recommended to store the product in a clean, dry environment to prevent packaging damage. Avoid placing it near volatile solvents. The optimal storage temperature is between 39-79°F (4-26°C), with a relative humidity of 40%–50%. Rotate inventory regularly to maintain product quality.

The test results provided above represent average values obtained under laboratory conditions and are intended for general reference only. JL3 does not guarantee the accuracy, completeness, or performance consistency of these results. These values do not constitute a warranty, either express or implied, including but not limited to warranties of performance, safety, or fitness for a particular purpose—whether the product is used alone or in combination with other materials. JL3 strongly recommends that users conduct independent testing to determine the product's suitability for their specific application prior to use. JL3 assumes no liability for any damage, loss, or injury arising from the use of this product. All sales are subject to JL3's standard terms and conditions. Product specifications and information are subject to change without prior notice.

Fujian Jialong Adhesive Tape Co.,Ltd.

No. 11 Xiazhai Road, Jiulong Industrial Park, Hua An Economic Development Zone, Hua An, Zhangzhou, Fujian 363000 China.

Tel:+86 596-728-0001

info@jl3tape.com

http://www.jl3tape.com